







4800

hand-drawn

for light and medium-weight curtains

Stable rail with elegant appearance

# 4800



### hand-drawn

for light and medium-weight curtains

### Stable & elegant

The Qurails 4800 is a very stable rail because of its shape. It emanates elegance and simplicity. The track can be easily mounted on a wall or ceiling in various ways. A very popular track that can be used in a wide variety of situations, such as private homes, but also in office buildings and in the care sector.

- The ideal track for sheers, medium-heavy or heavy curtains.
- Easy to bend and exceptional quality.
- Can be forward or reverse bent in different radii.
- Compatible with the Goelst Flow System for regularly pleated curtains.
- Silent and smooth running, also round bends.



### Standard colours





### High quality, wear-resistant coating, highly colourfast, UV-resistant. Other RAL colours & special coatings on request.

### **Features**


Material: aluminium

Colour: white, natural anodised

Dimensions: 21 x 13 mm
Weight profile: 231 gr/m<sup>1</sup>
Mounting: wall or ceiling

### **Profile specifications**

### Aluminium profile:



### Colours with RAL code and lengths (m):

	RAL	4	5	6	7
white	9010	•	•	•	•
natural				•	

### **Mounting surface:**

- wood
- masonry/concrete

### **Bracket type:**

- ceiling bracket
- wall bracket
- spacer bracket

### **Bending:**

bending radius	bending tool		
R 10 cm R 15 cm R>100 cm	1015 1015 1018		
R 10 cm			

#### **Flow**


The Qurails Flow System keeps pleats in curtains consistent. It can be used with small and wide channel tracks and, because of the broad assortment of components, it can be integrated in hand-drawn, cord-pulled and electrically operated systems.

The Flow System can also be used with curved curtain tracks. For further information, see the Flow product data sheet.


## Specification guide Material

- Aluminium EN AW-6060-T66.
- Anodised in accordance with the Qualanod standard.
- Powder coated in accordance with the Qualicoat standard.


### **Mounting**




Wall mounting with wall bracket 5351




Ceiling mounting with wall bracket 5350



Ceiling mounting with double bracket 2216 and ceiling support 5350



Method for uncoupling wall bracket 5351 and rail 4800






Mounting with extension brackets 2015, 2018 or 2019 in combination with ceiling bracket 5350

Detail front view of extension bracket

### **Application example**



Mounting to suspended ceiling by means of grid bracket, this application is not suitable for heavy curtains.

### Mounting guideline



The distance between the brackets can vary depending on the following factors: the mounting surface (wood, concrete or plaster), the weight of the curtains and the curtain fabric production method, the specific application and the system usage intensity. General advice: with the curtains open, place additional brackets where the pleats bunch together. Also place additional brackets before and after bends.

### Standard parts

#### **Curtain transport**



4001 end stop white / grey / black



4010 glider white / grey / black

### Mounting



5350 ceiling bracket white



5351 wall bracket white

### Accessories



4853 end cap white / grey



**4852** connecting bridge 6cm

### **Optional parts**

### **Curtain transport**



2004 brake glider white / grey / black



4001-M-N end stop metal with eye natural



4002 end stop metal



4003 spring stop plastic requires punch hole



4007 rotating glider white/ grey / silver / black



4007-LRS

rotating glider LRS grijs / rotating glider LRS red



4010-50 glider white with plastic hook 2023



4012 click-in glider white



4020 heavy duty glider white / grey / black



4074-1000 carrier with overlap, a.o. for draw rod white / natural metallic / black



4075-1000 carrier without overlap, a.o. for draw rod white / natural metallic / black



**2020** double hook white



**2021** G-Hook white



2022 curtain hook white



2023 curtain hook white



2024-55 adjustable sew in hook white 55mm



2024-95 adjustable sew in hook white 95mm

### Mounting



2050-SYST T-bar clip white for ceiling grid



2216
double bracket
white / natural metallic
/ black



2015 extension bracket 5, 7.5, 10, 15 cm white / natural metallic / black



2018
extension bracket
heavy duty15 cm
white / natural metallic



2019
extension bracket heavy
duty 20, 25, 30 cm
white / natural metallic /
zwart

#### **Accessories**



4048-12MM corner connection



**7399** plexiglass draw rod transparent

Technical specifications are subject to change without prior notice.
Copyright: Photography The Duke, Dré
Wouters, The Art of Living magazine

